

WP

COLD GALVANISER SPRAY



Weldable primer

BENEFITS

- Easy to use.
- For all touch up and repair jobs.
- Effective rust neutraliser.
- Prepare surfaces for welding.
- Protects ferrous metals in hostile environments.
- Conductive so permits welding.
- Bright metallic finish, resist salt spray.

PRODUCT SIZES

- 500ml aerosol
- 500ml aerosol (dozen)

DESCRIPTION

A fast-drying rust stabilising primer for all light to heavy rust surfaces.

Technically formulated to neutralise rust whilst giving the perfect surface to weld with.

Ideal for protection of bare iron and steel fabrications and restoring galvanic protection to galvanised metals following damage. Typically used on agricultural buildings and machinery, guttering, pipework and for protection of chassis and heavy machinery.

INSTRUCTIONS FOR USE

- Shake until the internal ball can be heard to move freely inside the can.
- Continue to shake for a further 1 – 2 minutes.
- Remove any rust, dirt, paint and primer from the area to be welded.
- Keeping can as upright as possible, spray from a distance of 20 – 30 cms.
- Drying time is 10-15 minutes.

HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H223 – Flammable aerosol.
H229 – Pressurised container. May burst if heated.
H315 – Causes skin irritation.
H319 – Causes serious eye irritation.
H332- Harmful if inhaled.
H336 – May cause drowsiness or dizziness.
H411- Harmful to aquatic life with long lasting effects.

HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

P102 – Keep out of reach of children.
P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 – Do not pierce or burn, even after use.
P261 – Avoid breathing vapours, spray, mist.
P264 – Wash hands thoroughly after handling.
P271 – Use only outdoors or in well ventilated area.
P273 – Avoid release to the environment.
P280 – Wear eye protection, protective gloves.
P302+P352 – IF ON SKIN: Wash with plenty of water.
P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312- Call a doctor, a POISON CENTRE, if you feel unwell.
P332+P313 – If skin irritation occurs: Get medical advice/attention.
P337+P313 – If eye irritation persists: Get medical advice/attention.
P362+P364 – Take off contaminated clothing and wash it before reuse.
P391 – Collect spillage.
P403+P233 – Store in a well-ventilated place. Keep container tightly closed.
P405 – Store locked up.
P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 – Dispose of contents/container to hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation.
Hazardous ingredients:
Acetone, propan-2-one, propanone; Cold Galvanising Coat.
EUH210 – Safety Data Sheet available on request.

PHYSICAL PROPERTIES

Colour: No data available.
Appearance: Liquid under pressure.
Odour: Characteristic.
Solubility: No data available.
Boiling point: <=35°C.
Flash point: -26°C.
Flammability: Flammable aerosol.
Extremely flammable aerosol.
Density: No data available.
pH: N/a.

Wessex Chemical Factors Ltd
17 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom

Tel: 01202 823699
Fax: 01202 813863
Email: info@wessexchemicalfactors.co.uk
Website: www.wessexboatstore.co.uk

