

# WP

# DMPS SILICONE SPRAY

Super rich silicone lubricant and mould release



## BENEFITS

- Water repellence.
- Odourless.
- Non- tainting.
- Non-staining.
- Safe on most surfaces.
- Provides a colourless, inert coating.

## PRODUCT SIZES

- 500ml aerosol
- 500ml aerosol (dozen)

## DESCRIPTION

DMPS Silicone Spray is used extensively as a release/anti-stick agent in the plastic injection and fibreglass moulding industries.

It may be used on oven shelves at temperatures below 315°C and has varied uses in the footwear and ceramics industries.

DMPS Silicone Spray is a non-staining, dry lubricant and is ideal for unsticking drawers and curtain tracks and has many applications where plastic bearings, synthetic and natural rubber, textile fabrics etc. need some form of lubrication.

The ability to impart a high gloss shine to vinyl, wood and metal surfaces makes DMPS Silicone Spray an ideal dashboard renovator and trim conditioner whilst helping to eliminate squeaks.

## INSTRUCTIONS FOR USE

Shake can before use.

Hold can as upright as possible and spray evenly over surface as required.

## HEALTH & SAFETY

### Hazard pictograms (CLP):



### Hazard statements (CLP):

H222 – Extremely flammable aerosol.  
H229 – Pressurised container: may burst if heated.  
H315 – Causes skin irritation.  
H336 – May cause drowsiness or dizziness.  
H411 – Toxic to aquatic life with long lasting effects

## PHYSICAL PROPERTIES

**Colour:** Colourless.

**Appearance:** Liquid under pressure.

**Odour:** No data available.

**Solubility:** insoluble in water.

**Boiling point:** No data available.

**Flash point:** <0°C.

**Flammability:** Extremely flammable aerosol.

**Density:** No data available.

**pH:** N/a.

**Wessex Chemical Factors Ltd**

**17 Crane Way**

**Woolsbridge Industrial Park**

**Three Legged Cross**

**Wimborne**

**Dorset**

**BH21 6FA**

**United Kingdom**

**Tel: 01202 823699**

**Fax: 01202 813863**

**Email: [info@wessexchemicalfactors.co.uk](mailto:info@wessexchemicalfactors.co.uk)**

**Website: [www.wessexboatstore.co.uk](http://www.wessexboatstore.co.uk)**



## HEALTH & SAFETY (Cont.)

### Precautionary statements (CLP):

P102 – Keep out of reach of children.  
P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 – Do not pierce or burn, even after use.  
P261 – Avoid breathing vapours, spray.  
P264 – Wash hands thoroughly after handling.  
P271 – Use only outdoors or in a well-ventilated area.  
P273 – Avoid release to the environment.  
P280 – Wear protective gloves.  
P302+P352 – IF ON SKIN: Wash with plenty of water.  
P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 – Call a doctor, a POISON CENTRE, if you feel unwell.  
P332+P313 – If skin irritation occurs: Get medical advice/attention.  
P362+P364 – Take off contaminated clothing and wash before reuse.  
P391 – Collect spillage.  
P403+P233 – Store in a well-ventilated place. Keep container tightly closed.  
P405 – Store locked up.  
P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 – Dispose of contents/container to hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation.  
**Hazardous ingredients:**  
Naphtha (petroleum), hydrotreated light, Low boiling point hydrogen treated naphtha. [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F).]  
**EUH210 – Safety Data Sheet available on request.**